





## Automatic Gate System for Residential


Reliable . Durable . Convenient & Intelligent




ARM-202



ARM-808



Swing Gate



Folding Gate

- Quality** 12-months manufacturer warranty.
- Reliability** Advanced microprocessor-based electronic low-voltage controller and distributor with auto-analysis and self-diagnostic functions encased in weather resistant housing.
- Safely** 12-volts DC motors eliminating the dangers of electric shock hazard and operating safely even in rains and floods.
- Security** Remote control transmitter and receiver with code encryption technology offering the finest security performance.
- Emergency** Instant panic alarm function operated through remote control. \*Optional
- Efficiency** Dual speed motors reducing to ultra low speed while reaching the ends of opening or closing the gate, eliminating any crushing impact.
- Protection** Electronic overload sensor provide instant stop upon contact with obstacle for extra protection to children and elderly on case of emergency.
- Convenience** Uninterrupted service with rechargeable back-up battery during power failure.
- Technology** The high-tech arms are installed above the ground, eliminating common problems of water getting into the motor. Besides, it provides multiple mounting choices (swing in/ out) to maximize entry/ exit clearance. Due to its self-machanical locking system, no solenoid lock is required, resulting in maintenance free advantages.


## Specifications

	ARM-202	ARM-808
Driving Method	Electro - Mechanical Screw Driver Pistron Type	
Operating Voltage	- High Speed DC 24V - Low Speed DC 12V	DC 16V DC 8V
Back-up Battery	12 Volt. 7AH Rechargeable Lead Acid Battery	
Safety Clutch	Electric Curent Sensing using Hi-Amp Auto Reserse	
Safety Barrier	Infrared beam sensor *Optional	
Electric Controller	Micro-processor based	
Manual Operation	Special released key during power failure	
Max. Weight of Gate	400kg per wing with force adjustable	
Max. Length of Gate	3.25 meters per wing	
Operating Temperature	0-55 C	

## Package of CNG Swing Gates




ARM-202 Package




ARM-808 Package

- 1 CNG Control Panel
- 2 CNG Transformer
- 3 12V7AH Rechargeable Lead Acid Battery
- 4 Weather proof PVC Box
- 5 1 pair of ARM-202/ 808
- 6 Brackets
- 7 Screws & Nuts
- 8 1 pair of Release Key
- 9 Stopper
- 10 Receiver for Remote Control
- 11 3 units of Remote Control (Transmitter)



## Dimension of the Actuator Arm



ARM-202



ARM-808



## Optional items for CNG Swing Gates



Photoelectric Beam Sensor



Push Button for  
Open/ Close Gate

DISTRIBUTED BY:

