

PC COMMUNICATOR

EP.P1.STD



PC COMMUNICATOR

EP.P1.STD

Technical Specification

Input voltage	12VDC
Current Consumption	100mA
Protection	Gas Discharge Arrestor 20KVA (on the communication output)
Interface	RS-485 (2 wire)
Maximum serial controller supported	16 units
Maximum output distance	1000m
Signal	RS-485 (Data + & Data -)
Baud rate	9600
Stop bits	1
Data bits	8
Parity	None
Operating Temperature	0 °C – 50 °C
Humidity	0 - 95 %
Dimension (W x L x H)	65mm x 92mm x 25mm
Casing material	ABS

Ordering Information

EP.P1.STD EntryPass PC Communicator



www.entrypass.net

Malaysia

No. 40, Jalan TPP 1/10, Taman Industri Puchong, Batu 12 Jalan Puchong, 47160 Puchong Selangor Darul Ehsan, Malaysia.
Tel : +603 8068 1929
Fax : +603 8062 6937
Email : info@entrypass.net

Singapore

No. 1, UBI View, #03-03, Focus ONE Building, Singapore 408555.
Tel : +65- 6841 7242
Fax : +65- 6841 3937
Email : info@entrypass.net

Indonesia

Jl. Raya Lodan No. 2, kompl. Ruko Lodan Centre Blok. P 10, Jakarta Utara 14430, Indonesia.
Tel : +62 21 6983 3153
Fax : +62 21 690 3005
Email : info@entrypass.net

A securityhub group company

