

HD-H656H

General Features

- * 1/3" Sony Super HAD CCD
- * 620 TV Line (Color), 700TV Line (B/W)
- * 0.00001 Lux (HSBLC) (OSD)
- * Digital Wide Dynamic Range
- * Iris Varifocal Lens (3.5-16mm)



SPECIFICATIONS

MODEL	HDPRO HD-H656H
Image Pick-Up Device	1/3" Sony Super HAD CCD
TV System	NTSC, PAL
Total Pixels	NTSC=811(H) * 508(V) / PAL=795(H) * 595(V)
Effective Pixels	NTSC=768(H) * 494(V) / PAL=752(H) * 582(V)
Scanning System	2:1 Interlace
Synchronization	Internal / Line Lock
O.S.D	Available
Backlight	BLC / HSBLC / Off Selectable
Resolution	620TV Lines(Color), 700TV Lines(B/W)
S/N (Y signal)	52dB (AGC Off, Weight On)
Min. Illumination	0.00001Lux F1.2(Sens-Up * 258X)
White Balance	ATW / AWB / Indoor / Outdoor / Manual / AWC
Electronic Shutter Speed	1/60sec ~ 1/120,000sec
Sense-Up	Auto / Fixed / Off(Selectable limit *2 ~ *258)
Gain Control	High, Middle, Low, Off Selectable
3 DNR	Off/On (1~50 Level Adjustable)
D-WDR	Indoor / Outdoor / Off
Motion Detection	On/Off (4 Zone, Alarm Output)
Privacy	On/Off (8 Zone)
Mirror	Off / Mirror / V-Rev / Rotate
Freeze	On / Off
Sharpness	0~31'(Level Adjustable)
D&N Selection	Color /Auto / Ext / BW
Digital Zoom	On(*32) / Off
Power Supply	DC 12V
Power Consumption	120MA
Lens	DC Auto Iris Varifocal Lens(3.5-12mm)
Operational Temp.	-10°C ~ +50°C(Heater On: -40°C ~ 50°C)
Storage Temp.	--20°C ~ +60°C
Weight	450g / 400g



YOUR'S SMART SECURITY PROVIDER

GENX TECHNOLOGY (M) SDN BHD

NO.68-2, JALAN DWITASIK, DATARAN DWITASIK, BANDAR SRI PERMAISURI, 56000 KUALA LUMPUR, MALAYSIA
TEL: 03-9171 1988 FAX:03-9171 4988

