



HD-N7300HTL

General Features

- * 1/3" Sony Super HAD CCD
- * True Day/Night with ICR
- * ø5 IR LED Built-in 63pcs
- * DC Auto Iris Varifocal Lens(2.8-12mm)
- * Highest Resolution:Vivid Sharp Picture in completely darkness
- * Full OSD Operation
- * 0Lux(IR LED On)
- * Dual Power(AC 24V / DC 12V)-Option

SPECIFICATIONS

MODEL	HDPRO HD-N7300HTL
Image Pick-Up Device	1/3" Sony Super HAD CCD
TV System	NTSC, PAL
Total Pixels	NTSC=1020(H) * 508(V) / PAL=1020(H) * 596(V)
Effective Pixels	NTSC=976(H) * 494(V) / PAL=976(H) * 582(V)
Scanning System	2:1 Interlace
Synchronization	Internal
O.S.D	Available
Backlight	OFF / HSBLC / BLC Selectable
Resolution	700TV Lines
S/N (Y signal)	52dB
Minimum Illumination	0Lux(IR LED ON)
White Balance	ATW
Electronic Shutter Speed	AUTO (1/50sec, 1/60sec ~ 1/100,000sec)
Sense-Up	Off / Auto(x2~x256)
Gain Control	High, Middle, Low, Off Selectable
3 DNR	3D-DNR(1~200 Level Adjustable)
D-WDR	Indoor / Outdoor / Off
Motion Detection	On / Off (4 Zones)
Privacy	On / Off (8 Zones)
Mirror	Off / Mirror / V-Rev / Rotate
Freeze	On / Off
Sharpness	0~31'(Level Adjustable)
D&N Selection	Color / BW / Auto/ EXT
Digital Zoom	On / Off(x1~x32)
DIS (Digital Image Stabilization)	On / Off
Power Supply	DC 12V
Power Consumption	IR LED ON:700mA Max
Lens	DC Auto Iris Varifocal Lens(2.8-12mm)
Operational Temp.	-10 ~ +50 Deg C. RH 95% Max.
Storage Temp.	-20 ~ +60 Deg C. RH 95% Max.
Dimension	66mm(W) * 67mm(H) * 77mm(D)
Weight	700g



YOUR'S SMART SECURITY PROVIDER

GENX TECHNOLOGY (M) SDN BHD

NO.68-2, JALAN DWITASIK, DATARAN DWITASIK, BANDAR SRI PERMAISURI, 56000 KUALA LUMPUR, MALAYSIA
 TEL: 03-9171 1988 FAX:03-9171 4988

