



Specs		Model
		ITVI-R16120TX
System	Compression	Standard H.264 High Profile
	OS	Embedded Linux
	Pentaplex	Live Display / Record / Playback / Backup / Remote Access
Video	Input	BNC x 16 CH
	Output	VGA x 1CH : 1080P HDMI x 1CH : 1080P ;
Audio	Input	RCA x 1CH
	Output	RCA x 1CH
	2- ways audio	take up 1 CH audio input
Record	Resolution	720P (1280 X 720) , 1080P (1920X 1080)
	Frame Rate	400fps (PAL) /480fps (NTSC)
		200fps (PAL) /240fps (NTSC)
	Bit Rate	1 M ~ 6 Mbps
	Encode	VBR / CBR
	Quality	6 level
	Mode	Manual, Timer, Motion, Sensor
File Management	Lock, Unlock, Reserving time, Redundancy	
Playback	Playback	8 CH
	Search	Time, Motion, Sensor, Single or Multi-channel
	Function	Play, Pause, FF, FB, Shutter Control ,Jog, Digital zoom
Alarm	Mode	Sensor, Motion, Video loss
	Input	\
	Output	\
	Triggering	Record, PTZ move, Relay out, E-mail, etc
Network	Interface	RJ 45
	Dual-stream	Individual Network Video Stream and local recording stream, set separately
	PTZ Protocol	Pelco D, Pelco P, RANGE, VISCA, DSCP, VIDO, STAR, NEON, MINKING, LILIN
	Protocol	TCP/IP.UDP, DHCP. DNS, PPPOE, DDNS,
	User	10 users online, dual stream
Cellphone	OS	Iphone, Blackberry, Android, Windows mobile
	Function	Multi-Channel display, Server list, Recording, PTZ, etc
I/O	HDD	SATA x2
	RS485	RS485 x1 (for PTZ or Keyboard)
	USB	USB2.0 x 2 (for mouse and USB backup device)
Others	Dimension	W430mm×D300mm×H55mm
	Accessory	Remote controller, SATA cable, USB mouse
	Power Supply	DC: 12V
	Working Environment	10°C ~50°C , 10% ~ 90%(Humidity)