AVTECH

AVC792D

4CH Full 960H DVR

FEATURES

Push Status - Active Event Notification with EagleEyes App

v Sends instant notifications for system events, such as video loss or HDD data removal

All-Channels 960H Video Recording

v Supports 960H video recording for all channels for evidentiary recording with high quality and clear images.

HDMI Video Output at 1080P Resolution

v Full HD video display through HDMI interface

Mobile Surveillance with EagleEyes App

v Compatible with iOS & Android mobile devices.

Remote Surveillance with Browsers and CMS

v For web browsers, compatible with Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera.

v For CMS software, available with our self-developed and free software, "Video Viewer.

v Applicable also to Apple's media player, QuickTime.

Independent Channel Control

v Definable "Resolution" / "Quality" / "IPS" by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

v Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

Multiplex

v Allows live display, record, playback, backup and network operation at the same time.

Backup Function

v Supports USB flash drive and network backup.

EagleEyes for Mobile Surveillance
Official Website : www.eagleeyescctv.com
Video Demo : 203.66.45.240/seo/video
Facebook : 203.66.45.240/seo/facebook

SPECIFICATIONS

q Video		
Video System		NTSC / PAL (auto detection)
Video Compression Format		H.264
Video Input		4 channels (Composite video signal 1 Vp-p 75Ω BNC)
Video Output	VGA	YES
	HDMI	YES
Dual Video Output		YES

q Record & Backup		
Maximum Recording Rate	960H	960x480 pixels with 120 IPS <NTSC> / 960 x 576 pixels with 100 IPS <PAL>
	Frame	704×480 pixels with 120 IPS <NTSC> / 704×576 pixels with 100 IPS <PAL>
	Field	704x240 pixels with 120 IPS <NTSC> / 704×288 pixels with 100 IPS <PAL>
	CIF	352×240 pixels with 120 IPS <NTSC> / 352×288 pixels with 100 IPS <PAL>
Recording Mode		Manual / Timer / Motion / Alarm / Remote
Pre-alarm Recording		YES
Quick Search		Time / Motion / Alarm search mode
Backup Device		USB 2.0 flash drive / Network

q Audio	
Audio Input	4 audio inputs
Audio Output	1 audio output (Mono)

q General	
Hard Disk Storage	Accommodates up to 1 SATA HDD (1 HDD capacity up to 3TB)
SATA Interface	YES
Image Quality Setting	SUPER BEST / BEST / HIGH / NORMAL
USB Mouse Control	YES
Motion Detection Area	16 × 12 grids per channel
Motion Detection Sensitivity	3 adjustable parameters for accurate detection
Event Notification	FTP / E-Mail
Picture Zoom	2X digital zoom
PTZ Control	YES
Alarm I/O	4 inputs, 1 output
IR Remote Control	YES (IR receiver built-in)
Key Lock (Password Protection)	YES
User Level	4 user levels for different access privilege
Video Loss Detection	YES
Camera Title	Supports up to 12 letters
Video Adjustable	Hue / Saturation / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY & MM/DD/YY
Daylight Saving	YES
Power Source (±10%)	DC12V / 3A
Power Consumption (±10%)	5W (without hard disk & camera)
Operating Temperature	10℃ ~ 40℃ (50℉~104℉)
Dimensions (mm)**	375(W) × 61(H) × 281(D)

q Network	
Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS

SPECIFICATIONS

q Remote Surveillance from PC

Compatible Operating System	Windows & MAC	
Compatible Program	Web Browser:	Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera
	Video Viewer:	For both Windows and MAC operating systems
	QuickTime	For both Windows and MAC operating systems
Max. online users	10	
Web Transmitting Compression Format	H.264	
Network Live Audio	YES	
Remote Independent Operation	YES	
Remote Event Download & Playback	YES	
R.E.T.R. (Remote Event Trigger Recording)	YES	

q Mobile Surveillance

App	EagleEyes
Compatible Devices	iOS & Android devices
Push Status	YES (With EagleEyes for iPhone, iPad, Android versions)

q Others

AVTECH Free DDNS service	YES
Multiplex Operation	Live display / record / playback / backup / network operations
System Recovery	System auto recovery after power failure
Optional Peripherals	Keyboard Controller

*The specifications are subject to change without notice.
** Dimensional tolerance: ±5mm

REAL PANEL