

EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com Video Demo : www.eagleeyescctv.com/video Facebook : www.eagleeyescctv.com/facebook

AVC795HA

8CH Full 960H DVR

Push Video + Push Status + Full 960H Video Recording + 1080P HDMI



FEATURES

> Push Video & Push Status - Active Event Notification with EagleEyes App

- Push Video to send instant notifications for an alarm event when an alarm device is connected to the DVR.
- Push Status to send instant notifications for system events, such as video loss or HDD data removal.

> All-Channels 960H Video Recording

• Supports 960H video recording for all channels for evidentiary recording with high quality and clear images.

> HDMI Video Output at 1080P Resolution

• Full HD video display through HDMI interface.

> Mobile Surveillance with EagleEyes App

- · Compatible with iOS & Android mobile devices.
- > Remote Surveillance with Browsers and CMS
 - For web browsers, compatible with Internet Explorer, Mozilla Firefox, Google Chrome & Safari.
 - For CMS software, available with our self-developed and free software, "Video Viewer.
 - Applicable also to Apple's media player, QuickTime.

External Disk Array Support for More Video Storage

 eSATA interface built-in to connect a disk array (up to 4-bay disk array with RAID 0 and 1) for more video storage

> Independent Channel Control

• Definable "Resolution" / "Quality" / "IPS" by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

• Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

> Multiplex

• Allows live display, record, playback, backup and network operation at the same time.

Backup Function

• Supports USB flash drive and network backup.



EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com

Video Demo : www.eagleeyescctv.com/video

: www.eagleeyescctv.com/facebook

O SPECIFICATIONS

Video System NTSC / PAL (auto detection) Video Compression Format 8 channels (Composite video signal 1Vp-p750_BNC) Video Output BNC YES (Call monito for sequence display) Video Output BNC YES Dual Video Output VEA YES Maximum Recording Rate 960H 960 x 480 pixels with 240 IPS <ntsc> 1960 x 576 pixels with 200 IPS <pal> Maximum Recording Rate 960H 960 x 480 pixels with 240 IPS <ntsc> 704+576 pixels with 200 IPS <pal> France 704+240 pixels with 240 IPS <ntsc> 704+576 pixels with 200 IPS <pal> Recording Mode France 704+240 pixels with 240 IPS <ntsc> 704+576 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording Pre-alarm Recording YES Manual / Timer / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network V Vadio 4 audio input1 1 audio output (Mono) VEG General Up to 1 SATA HDD SATA Interface Wadio SUPER DEST / BEST / BEST / BEST / HIGH / NORMAL SUBS Mouse Control Motion Detection Area 1 6 × 12 grids per channal</pal></ntsc></pal></ntsc></pal></ntsc></pal></ntsc>	▼ Video						
Video Input 8 channels (Composite video signal 1 Vp-p 75Ω BNC) Video Output BNC YES (Call monitor for sequence display) Video Output YES Dual Video Output YES Maximum Recording Rate 960 x 480 pixels with 240 IPS <ntsc> / 960 x 576 pixels with 200 IPS <pal> Frame 704×480 pixels with 240 IPS <ntsc> / 704×286 pixels with 200 IPS <pal> Field 704×480 pixels with 240 IPS <ntsc> / 704×286 pixels with 200 IPS <pal> CIF 352×240 pixels with 240 IPS <ntsc> / 704×286 pixels with 200 IPS <pal> Recording Mode Manual / Time / Motion / Alarm / Renote Pre-alarm Recording YES Quick Search USB 2.0 flash drive / Network V Audio USB 2.0 flash drive / Network V Audio 4 audio inputs Audio Input 4 audio output for external disk array connection) Image Coulity Setting SUPER BEST / HICH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Area<td></td><td></td><td></td><td>NTSC / PAL (auto detection)</td></pal></ntsc></pal></ntsc></pal></ntsc></pal></ntsc>				NTSC / PAL (auto detection)			
Video Output BNC YES (Call monitor for sequence display) VGA YES Dual Video Output YES Dual Video Output YES W Record & Backup 960H Maximum Recording Rate 960H Finance 704x240 pixels with 240 IPS <ntsc> / 704x576 pixels with 200 IPS <pal> Field 704x240 pixels with 240 IPS <ntsc> / 704x576 pixels with 200 IPS <pal> CIF 352x240 pixels with 240 IPS <ntsc> / 704x288 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Pre-alarm Recording YES Audio Unput 4 audio inputs Audio Unput YES (For external disk array connection) Mation Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Mot</pal></ntsc></pal></ntsc></pal></ntsc>				H.264			
VGA YES Dual Video Output YES Dual Video Output YES Maximum Recording Rate 960 x 490 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> Frame 704×480 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> Field 704×280 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> Recording Mode Frame 704×280 pixels with 240 IPS <ntsc> / 352×280 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Molion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Molion / Alarm search mode Backup Device USB 2.0 flash drive / Network V Audio 4 audio inputs 4 audio inputs Audio Uput 1 audio output (Mono) V General Up to 1 SATA HDD SATA Interface YES SATA Interface USB Mouse Control YES VES / Backup Device YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST</pal></ntsc></pal></ntsc></pal></ntsc></pal></ntsc>	Video Input			8 channels (Composite video signal 1 Vp-p 75 Ω BNC)			
HDMI YES Dual Video Output YES ✓ Record & Backup 960H 960 x 480 pixels with 240 IPS <ntsc> / 960 x 576 pixels with 200 IPS <pal> Maximum Recording Rate 960H 960 x 480 pixels with 240 IPS <ntsc> / 704 x576 pixels with 200 IPS <pal> Field 704 x430 pixels with 240 IPS <ntsc> / 704 x588 pixels with 200 IPS <pal> CIF 352 x240 pixels with 240 IPS <ntsc> / 352 x288 pixels with 200 IPS <pal> Pre-alarm Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Output 1 audio output (Mono) ✓ General YES Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES Motion Detection Area 16 * 12 grids per channel Motion Detection Area 16 * 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputts</pal></ntsc></pal></ntsc></pal></ntsc></pal></ntsc>	Video Output	BNC		YES (Call monitor for sequence display)			
Dual Video Output YES Maximum Recording Rate 960 x 480 pixels with 240 IPS <ntsc> / 960 x 576 pixels with 200 IPS <pal> Field 704×480 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> CIF 352×240 pixels with 240 IPS <ntsc> / 704×288 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network V Audio 4 audio input Audio Input 4 audio input Audio Output 1 audio output (Mono) V General YES Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Picture Zoom 2X digital zoom PIZ Control YES IR Remote Control YES Use Level 4 user levels for different access privilege Video Loss Detection YES Alarm I/O 8 inputs (2 inputs for PL = Mail IR Remote Control YES Control YES</pal></ntsc></pal></ntsc></pal></ntsc>				YES			
▼ Record & Backup Maximum Recording Rate 960 × 480 pixels with 240 IPS <ntsc> / 960 × 576 pixels with 200 IPS <pal> Frame 704×480 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> CIF 352×240 pixels with 240 IPS <ntsc> / 704×288 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio input Audio Output 1 audio output (Mono) ✓ General Up to 1 SATA HDD Hard Disk Storage* Up to 1 SATA HDD SATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Pixel Voteo / FIP / E-Mail Picture Zoom Picture Zoom YES Alarm I/O 8 inputs for Push Video), 1 output IR Remote Control YES</pal></ntsc></pal></ntsc></pal></ntsc>		HDMI		YES			
Maximum Recording Rate 960H 960 x 480 pixels with 240 IPS <ntsc> / 960 x 576 pixels with 200 IPS <pal> Frame 7/04×480 pixels with 240 IPS <ntsc> / 7/04×286 pixels with 200 IPS <pal> CIF 352×240 pixels with 240 IPS <ntsc> / 7/04×286 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm / Remote Backup Device USB 2.0 flash drive / Network V Audio 4 audio inputs Audio Output 1 audio output (Mono) V General YES Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Area 2 x digital zoom PIZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel</pal></ntsc></pal></ntsc></pal></ntsc>							
Frame 704×480 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> Field 704×240 pixels with 240 IPS <ntsc> / 704×280 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network V Audio 4 audio inputs Audio Uput 1 audio output (Mono) V General YES Bard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Area 2X digital zoom PTZ control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Data Interface YES Motion Detection Area 16 × 12 grids per channel Motion Det</pal></ntsc></pal></ntsc>							
Frame 704×480 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal> Field 704×240 pixels with 240 IPS <ntsc> / 704×280 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network V Audio 4 audio inputs Audio Uput 1 audio output (Mono) V General YES Bard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Area 2X digital zoom PTZ control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Data Interface YES Motion Detection Area 16 × 12 grids per channel Motion Det</pal></ntsc></pal></ntsc>	•		ЭН	960 x 480 pixels with 240 IPS <ntsc> / 960 x 576 pixels with 200 IPS <pai></pai></ntsc>			
Field 704x240 pixels with 240 IPS <ntsc> / 704×288 pixels with 200 IPS <pal> Recording Mode Manual / Time / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Output 1 audio output (Mono) ✓ General Hard Disk Storage** Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES Guity Setting SUPE BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output I'R Remote Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output I'R Remote Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output I'R Remote Control YES Alarm I/O 8 inputs (2 inputs for Hannel User Level <td< td=""><td colspan="2"></td><td>ame</td><td></td></td<></pal></ntsc>			ame				
CIF 352×240 pixels with 240 IPS <ntsc> / 352×288 pixels with 200 IPS <pal> Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Upput 4 audio output (Mono) ✓ General 1 Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES eSATA Interface YES eSATA Interface YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / TP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Marou Detection YES Camera Title Supports up to 12 letters Video Adjustable Huter / Suturation / Contrast / Brightness</pal></ntsc>		Fie	ld				
Recording Mode Manual / Timer / Motion / Alarm / Remote Pre-alarm Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Output 1 audio output (Mono) ✓ General 1 Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES SATA Interface YES (For extremal disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Nouse Control YES Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Pitz Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Adjustable YES Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Date Display Format YY/MM/DD, DD/M/YY & M/DY/Y Date Display Format YY/MM/DD, DD/M/YY & M/DY/Y							
Pre-alam Recording YES Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Output 1 audio output (Mono) ✓ General 1 Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES eSATA Interface YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Adjustable Hue / Saturation / Contrast / Brightness Datingth Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Level Y//MM/DD, DD//MM/YY & MM/DD/YY Date Level	Recording Mode						
Quick Search Time / Motion / Alarm search mode Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Uutput 1 audio output (Mono) ✓ General 1 Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Udeo Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Daty Interface YY/MM/DD, DD/MM/Y & MM/D/YY Daty Interface YY/MM/DD, DD/M/YY & SM/HD/YY <tr< td=""><td colspan="3"></td><td colspan="3"></td></tr<>							
Backup Device USB 2.0 flash drive / Network ✓ Audio 4 audio inputs Audio Output 1 audio output (Mono) ✓ General 1 audio output (Mono) Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES Image Quality Setting SUPER BEST / BEST / HEG/ NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PIZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Udeo Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MMUDD, DD/MYY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19Y / 2.1A Power Consumption (±10%) <td< td=""><td></td><td></td><td></td><td colspan="3"></td></td<>							
▼ Audio Audio Input 4 audio inputs Audio Output 1 audio output (Mono) ▼ General Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES work YES eSATA Interface YES Mation Detection Area 16 × 12 grids per channel Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Pitctre Zoom 22 digital zoom PTZ Control YES Alarm I/O 8 inputs							
Audio Output 1 audio output (Mono) ✓ General Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Querer Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) 0.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D)	•						
▼ General Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Pitz Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Ude Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°T ~ 104°T) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network Ethernet 1000 Base-T. Supports rem	Audio Input			4 audio inputs			
Hard Disk Storage** Up to 1 SATA HDD SATA Interface YES eSATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (rmm)** 343(W) x 59(H) x 223(D)	· ·			1 audio output (Mono)			
SATA Interface YES eSATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D)	▼ General						
eSATA Interface YES (For external disk array connection) Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Publy Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50° ~ 104°F) Dimensions (mm)** 343(W) × 59(H) × 223(D)	Hard Disk Storage**			Up to 1 SATA HDD			
Image Quality Setting SUPER BEST / BEST / HIGH / NORMAL USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D)	· · · · · · · · · · · · · · · · · · ·						
USB Mouse Control YES Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MMYY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) V Network Ethernet	eSATA Interface			YES (For external disk array connection)			
Motion Detection Area 16 × 12 grids per channel Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Meter Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) V Network Ethernet 1000 Base-T. Supports remote control and live view via Ethernet							
Motion Detection Sensitivity 3 adjustable parameters for accurate detection Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES Vest Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) Vestwork 1000 Base-T. Supports remote control and live view via Ethernet				YES			
Event Notification Push Video / FTP / E-Mail Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES (IR receiver built-in) Key Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet				16 × 12 grids per channel			
Picture Zoom 2X digital zoom PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES (IR receiver built-in) Key Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) V Network Ethernet 1000 Base-T. Supports remote control and live view via Ethernet				3 adjustable parameters for accurate detection			
PTZ Control YES Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES (IR receiver built-in) Key Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Event Notification			Push Video / FTP / E-Mail			
Alarm I/O 8 inputs (2 inputs for Push Video), 1 output IR Remote Control YES (IR receiver built-in) Key Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Picture Zoom			2X digital zoom			
IR Remote Control YES (IR receiver built-in) Key Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	PTZ Control			YES			
Key Lock (Password Protection) YES User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Alarm I/O			8 inputs (2 inputs for Push Video), 1 output			
User Level 4 user levels for different access privilege Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	IR Remote Control						
Video Loss Detection YES Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Key Lock (Password Protection)						
Camera Title Supports up to 12 letters Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	User Level						
Video Adjustable Hue / Saturation / Contrast / Brightness Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Video Loss Detection						
Date Display Format YY/MM/DD, DD/MM/YY & MM/DD/YY Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Camera Title			Supports up to 12 letters			
Daylight Saving YES Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet	Video Adjustable			5			
Power Source (±10%) DC 19V / 2.1A Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet							
Power Consumption (±10%) 10.5W (without hard disk and camera) Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet							
Operating Temperature 10°C ~ 40°C (50°F ~ 104°F) Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet							
Dimensions (mm)** 343(W) x 59(H) x 223(D) ▼ Network 1000 Base-T. Supports remote control and live view via Ethernet							
▼ Network Ethernet 1000 Base-T. Supports remote control and live view via Ethernet							
Ethernet 1000 Base-T. Supports remote control and live view via Ethernet	Dimensions (mm)**			343(W) x 59(H) x 223(D)			
	▼ Network						
Network Protocol TCP/IP_PPPOF_DHCP and DDNS	Ethernet						
	Network Protocol			TCP/IP, PPPOE, DHCP and DDNS			



EagleEyes for Mobile Surveillance

Official Website : www.eagleeyescctv.com : www.eagleeyescctv.com/video

: www.eagleeyescctv.com/facebook

O SPECIFICATIONS

▼ Remote Surveillance from PC							
Compatible Operating System	Windows & MAC						
Compatible Program	Web Browser:	Internet Explorer, Mozilla Firefox, Google Chrome & Safari					
	Video Viewer:	For both Windows and MAC operating systems					
	QuickTime	For both Windows and MAC operating systems					
Max. online users	10						
Web Transmitting Compression Format	H.264						
Network Live Audio	YES						
Remote Independent Operation	YES						
Remote Event Download & Playback	YES						
R.E.T.R. (Remote Event Trigger Recording)	YES						
▼ Mobile Surveillance							
Арр		EagleEyes					
Compatible Devices	iOS & Android devices						
Push Video & Push Status	YES (With EagleEyes for iOS & Android devices)						
▼ Others							
AVTECH Free DDNS service	YES						
Multiplex Operation	Live display / record / playback / backup / network operations						
System Recovery	System auto recovery after power failure						
Optional Peripherals		Keyboard Controller					

* The specifications are subject to change without notice. ** 1 HDD capacity up to 4TB *** Dimensional tolerance: ±5mm

O REAR PANEL

